

CABAA

for defense



- 150 °C series, high heat resistance, lead type.
- Low ESR, high frequency and low impedance.
- Military products meet environmental requirements such as vibration and low air pressure. It can be supplied according to the "seven specialty" level, and can also be supplied according to the "general military" level.
- It is suitable for energy storage, filtering and bypass in electronic circuits in aerospace, aviation, cold, high altitude and ocean.
- Main technical indicators

Item	characteristic	
Operating temperature range	-55°C~+150°C	
Rated operating voltage range	16V~63V	
Nominal capacitance range	27μF~1000μF	
Allowable deviation of nominal capacitance	M (±20%) (25°C, 120Hz)	
DC leakage current *1	I ≤ 0.01C _R U _R (μA) (25°C, 2min) C _R : Nominal capacitance (μF); U _R : Rated voltage (V)	
The tangent of the loss angle tgδ (max)	For details, please refer to the "List of Product Specifications and Technical Parameters" (25°C, 120Hz)	
ESR (maximum) *2	For details, please refer to the "List of Product Specifications and Technical Parameters" (25°C, 100KHz)	
Durability (High Temperature Test)	The rated voltage is applied at 105 °C for 2000h, and after recovery for 24h, the electrical performance of the rated voltage (25 °C±5 °C) is tested at room temperature.	
	Rate of change in capacitance	≤± 10% of the initial measurement
	DC leakage current	≤ initial prescriptive value
	The loss angle is tangent	≤ 200% of the initial measurement
	ESR	≤ 200% of the initial measurement
Store at high temperatures	After storage at 105 °C for 500 hours, recovery for 24 hours, and test at room temperature (25 °C±5 °C), its electrical properties meet the following requirements:	
	Rate of change in capacitance	≤± 10% of the initial measurement
	DC leakage current	≤ 200% of the initial specified value
	The loss angle is tangent	≤ initial measurements
	ESR	≤ 200% of the initial measurement

Executive standard number: Q/MN60032-2023 Seventh special standard number: QZJ840634

Note: *1 1KΩ protection resistor in series during testing and charging; *2 The test location is the root of the capacitor lead terminal.

■ Outline drawing and size table (mm)

D×L	F±0.5	d±0.05	a
8×8	3.5	0.6	1.0
8×10	3.5	0.6	1.0
8×12	3.5	0.6	1.0
10×10	5	0.6	2.0
10×12.5	5	0.6	2.0

CDBAA

for defense

■ List of product specifications and technical parameters

rated voltage V	capacity μ F	Dimensions D×L (mm)	$tg\delta$ (120Hz)	ESR (m Ω ,25 $^{\circ}$ C) (100kHz)	Ripple current mA,rms (100KH, 150 $^{\circ}$ C)
16	270	8×8	0.08	30	800
	330	8×10	0.08	17	1900
	390	8×10	0.08	17	1900
	470	8×12	0.08	16	2000
	560	10×10	0.08	16	2000
	680	10×10	0.08	16	2000
	820	10×12.5	0.08	13	2200
	1000	10×12.5	0.08	13	2200
20	180	8×8	0.08	39	600
	220	8×8	0.08	39	600
	270	8×10	0.08	20	1800
	330	8×12	0.08	18	1900
	390	10×10	0.08	18	1900
	470	10×10	0.08	18	1900
	560	10×12.5	0.08	15	2100
	25	100	8×8	0.08	41
120		8×8	0.08	41	600
150		8×10	0.08	20	1800
180		8×12	0.08	19	1900
220		10×10	0.08	19	1900

rated voltage V	capacity μ F	Dimensions D×L (mm)	$tg\delta$ (120Hz)	ESR (m Ω ,25 $^{\circ}$ C) (100kHz)	Ripple current mA,rms (100KH, 150 $^{\circ}$ C)
25	270	10×10	0.08	19	1900
	330	10×12.5	0.08	15	2100
35	82	8×8	0.08	44	600
	100	8×10	0.08	22	1700
	120	8×12	0.08	21	1800
	150	8×12	0.08	21	1800
	180	10×10	0.08	21	1800
	220	10×12.5	0.08	16	2000
50	47	8×8	0.08	40	600
	56	8×10	0.08	35	1500
	68	8×12	0.08	30	1500
	82	10×10	0.08	25	1500
	100	10×12.5	0.08	22	1600
	120	10×12.5	0.08	22	1600
63	27	8×8	0.08	52	400
	33	8×10	0.08	38	1300
	39	8×10	0.08	38	1300
	47	8×12	0.08	35	1300
	56	10×10	0.08	28	1400
	68	10×12.5	0.08	25	1500

■ Ripple current frequency coefficient

Frequency (f)	1KHz≤f<1KHz	1KHz≤f<10KHz	10KHz≤f<100KHz	100KHz≤f<300KHz
coefficient	0.05	0.3	0.7	1.0

PART NUMBER EXAMPLE

CDBAA 477 M 1C T 080117

